



Visual and audio change filter alarms.



Optional Aluminum Duct

1300 / 2000 CFM Negative Air

HEPA-AIRE Negative Air Machines from Abatement Technologies® feature high-quality, galvanized steel cabinets and watertight pop rivet construction. Best suited for abatement, remediation and health care applications.

Specification

Dimensions	35 3/4"L x 26"W x 30 1/4"H - Optional hood 11"L x 23"W x 23"H
Weight	124 lbs. with H242406-99 HEPA 151 lbs. with H2010M HEPA
Power	120 VAC, 60 Hz, 15 Amps
Filters	<ul style="list-style-type: none"> • First stage filter: 1" coarse particulate polypad pre-filter. • Second stage filter: 2" pleated particulate pre-filter. • Optional second stage filter: 2" high capacity carbon filter. • Third stage HEPA filter: Tested and certified to an efficiency of 99.97% or higher against 0.3 micron size particles. • Optional Third stage HEPA filter: Tested and certified to an efficiency of 99.97% or higher against 0.3 micron size particles.

Features

Visual "change filter" indicator lamp.

Equipped with a differential pressure gauge and an audible "change filter" alarm

Four heavy-duty 4" casters (2 fixed and 2 locking swivel).

NEG2000-01, NEG2000-02, NEG2000-03, NEG2000-04